



**Advanced Card Systems Ltd.**  
Card & Reader Technologies

# ACR89U-A1 Handheld Smart Card Reader



Technical Specifications V1.24



## Table of Contents

<b>1.0.</b>	<b>Introduction .....</b>	<b>3</b>
<b>2.0.</b>	<b>Features .....</b>	<b>4</b>
<b>3.0.</b>	<b>Supported Card Types.....</b>	<b>5</b>
3.1.	MCU Cards .....	5
3.2.	Memory-based Smart Cards (Synchronous Interface).....	5
<b>4.0.</b>	<b>Typical Applications .....</b>	<b>6</b>
<b>5.0.</b>	<b>Technical Specifications .....</b>	<b>7</b>



## 1.0. Introduction



As smart card technology becomes more widely accepted in the market, developers find an opportunity to offer better usage experience and security by adding more features to smart card reading devices. In this light, the new ACR89U-A1 is a contact smart card reader that features a keypad, as well as an optional thermal printer to bring optimal security and convenience in many types of smart card application.

ACR89U-A1 is an electronic device designed primarily to operate in both office and field-based environments using PC-linked and standalone modes, respectively. It comes with a built-in keypad, LCD, rechargeable battery and large programmable memory features. ACR89U-A1 is a reliable reader that can support the rigorous performance requirements of highly demanding smart card applications, though operates under low energy consumption.

ACR89U-A1 also supports Secure PIN Entry (SPE) which allows users to securely input data such as PIN, through the device's PIN-pad. This security measure prevents PINs from getting exposed to a vulnerable PC or workstation, and successfully eliminates the possibility of Virus/Trojan or USB Sniffer getting hold of them.

Furthermore, ACR89U-A1 has User Firmware Upgradeability that can be done through its USB Interface. This capability makes ACR89U-A1 very accessible and ideal for many applications.



## 2.0. Features

- 32-bit RISC Processor running on Embedded FreeRTOS
- USB Firmware Upgradability
- Handheld size and weight
- Two Full-sized Contact Card Slots
- Three SIM-sized SAM Card Slots
- Dual Operation Modes:
  - PC-linked
  - Standalone
- PC-linked Operation:
  - USB 2.0 Full Speed Interface
  - Through detachable USB Cable
  - CCID Compliance
  - Supports PC/SC
- Standalone Operation:
  - Rechargeable Li-ion Battery (charging through USB)
  - Supports third party application programming via FreeRTOS
  - User-programmable in C language
- Built-in Peripherals:
  - Easy-to-Read, High Resolution Backlit LCD
  - Highly Durable Chemical Resistant Keypad
  - Four LED Status Indicators
  - Monotone Buzzer
  - Real-time Clock (RTC) with independent backup battery
  - Optional Detachable Thermal Printer (PTR89)
- Tamper Detection Switch to protect against unauthorized intrusion
- Supports Secure PIN Entry (SPE)
- Supports PPS (Protocol and Parameters Selection) with 115,200 BPS – 206,451 BPS in reading and writing smart cards
- Supports Android™ 3.1 and above
- Compliant with the following standards:
  - ISO 7816
  - PC/SC
  - CCID
  - USB Full Speed
  - CE
  - FCC
  - RoHs
  - EMVCo Level 1
  - Microsoft® WHQL



## 3.0. Supported Card Types

### 3.1. MCU Cards

The ACR89U-A1 operates with MCU cards that follow:

- T=0 or T=1 protocol
- ISO 7816 Compliant Class A, B, C (5 V, 3 V, 1.8 V)

### 3.2. Memory-based Smart Cards (Synchronous Interface)

The ACR89U-A1 supports the following memory cards:

- Cards following the I2C bus protocol (free memory cards) such as:
  - Atmel: AT24C01/02/04/08/16
- SLE4432/5542 intelligent 256 bytes EEPROM with write-protect function:
  - SLE4432, SLE5542
- SLE4418/5528 intelligent 1 KB EEPROM with write-protect function:
  - SLE4418, SLE5528

**Note:** Memory card supports ICC0 slot (front slot) only.



## 4.0. Typical Applications

- e-Healthcare
- e-Government
- e-Banking and e-Payment
- Transportation
- Loyalty Program
- Time and Attendance Checking





**Connectivity**

USB ..... USB Full Speed 2.0 (Type A; via detachable USB cable)

**Contact Smart Card Interface**

Standard ..... ISO 7816 Class A, B, C (5 V, 3 V, 1.8 V), T=0 and T=1  
 Supply Current ..... Max. 60 mA  
 Smart Card Read/Write Speed..... 12,903 BPS - 206,451 BPS (primary/secondary slot)  
 Clock Frequency ..... 4.8 MHz  
 Card Connector Type..... ICC Slot 0: Landing; ICC Slot 1: Contact  
 Card Insertion Cycles..... Min. 300,000/100,000 (primary/secondary slot)  
 Short Circuit Protection ..... +5 V/GND on all pins

**SAM Card Interface**

Number of SAM Card Slots ..... 3  
 Card Connector Type..... Contact  
 Smart Card Read/Write Speed..... 12,903 BPS - 206,451 BPS

**Built-in Peripherals**

Keypad ..... 20 keys  
 LCD Display ..... 128 pixels x 64 pixels Black and White Graphic LCD with Backlight  
 Number of characters: 8 line x 21 characters  
 Window size: 49 mm x 29 mm; Active area size: 46 mm x 28 mm  
 Buzzer ..... Monotone  
 LED Status Indicators ..... Four user-controllable LEDs  
 LED Colors ..... Red, Green and Yellow  
 Detachable Printer Cradle ..... PTR89 (optional)

**Physical Specifications**

Dimensions ..... Device: 181.5 mm (L) x 77.0 mm (W) x 30.5 mm (H)  
 Case Color ..... Black  
 Weight ..... Device: 235 g

**Operating Conditions**

Temperature ..... 0 °C – 50 °C  
 Humidity ..... 10% – 90%, non-condensing

**Application Programming Interface**

PC-linked Mode..... PC/SC  
 Standalone Mode ..... FreeRTOS

**Other Features**

Real-time Clock  
 Tamper Switch (internal anti-intrusion detections and protection)  
 USB Firmware Upgradability

**Certifications/Compliance**

CE, FCC, RoHS, ISO 7816, PC/SC, CCID, EMVCo Level 1,  
 Microsoft® WHQL for Windows® 2000, Windows® XP, Windows Vista®, Windows® 7, Windows® 8,  
 Windows® 8.1, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server  
 2012, Windows® Server 2012 R2

**Device Driver Operating System Support**

Windows® 2000, Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1,  
 Windows® Server 2003, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server 2012,  
 Windows® Server 2012 R2  
 Linux®, Mac OS®, Android™ 3.1 and above

